



REVISIONS					
REV	DATE	ECN #	DESCRIPTION	BY	APPD

**MOUNTING HOLE NOTES:**

1. LOCATED ON A  $\phi 7.25[184.15]$  ON THE ALUMINUM CLAMP.
2. FOUR (4) THRU HOLES AT  $\phi .688[17.46]$  EQUALLY SPACED  $90^\circ$  APART.

**PORCELAIN NOTES:**

1. WET PROCESS ELECTRICAL PORCELAIN.
2. GRAY GLAZE MUNSELL 5BG 7.0/0.4
3. TOLERANCE  $\pm 3\%$  WITH NOTHING LESS THAN  $\pm .03"$ , UNLESS OTHERWISE NOTED ON DRAWING.

**SPECIFICATIONS:**

1. VOLTAGE RATING ..... 15KV CLASS
2. BASIC IMPULSE LEVEL .....110KV BIL
3. NOMINAL CURRENT RATING ..... 630 AMPS
4. CREEP DISTANCE (MINIMUM) .....14.40 [365.76]
5. STRIKE DISTANCE (MINIMUM) .....7.67 [194.82]
6. APPROXIMATE WEIGHT .....30.36 LBS
7. CANTILEVER WITHSTAND LOAD.....230LBS

**MATERIAL:**

STUD - COPPER C11000  
SPADE - C84400 TIN PLATED

**NOTES:**

1. SHANK TO FIT INTO  $\phi 4-1/4"$  TANK HOLE.
2. FOR HORIZONTAL OR VERTICAL MOUNTING.
3. MINIMUM COLD OIL LEVEL - 4" UP SHANK.

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF H-J ENTERPRISES, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF H-J ENTERPRISES, INC. IS PROHIBITED.

**TOLERANCES (EXCEPT AS NOTED)**

DECIMAL  
X" =  $\pm .1"$   
.XX" =  $\pm .06"$   
.XXX" =  $\pm .03"$

ANGULAR  
+/- 1 Degrees



**H - J ENTERPRISES, INC.**  
3010 HIGH RIDGE BLVD. HIGH RIDGE, MO. 63049 USA  
PHONE 1-636-677-3421 FAX 1-636-376-1915

**15 KV CLASS POWER BUSHING (SINGLE PACK)**

MATERIAL (SEE DRAWING)

CHK'D \_\_\_\_\_ APP'D \_\_\_\_\_  
SCALE N.T.S.

DRAWING NO.  
**AS1721-021**

DRAWN BY **MAD** DATE **10/13/2020**