



NOTES:
1. ALL CONTACT SURFACES TO BE CLEAN & FREE FROM FLASH

MATERIAL:
1. E07 - CYCLOALIPHATIC EPOXY (U.V. EXPOSED), COLOR: GREY
2. HD ETP C11000 GRADE COPPER, SILVER OR TIN PLATED

SPECIFICATIONS:
1. MANUFACTURED IN ACCORDANCE WITH IEC 137-1995, CAN/CSA-C88.1-96, IEEE C57.19.01-1991
2. RATED VOLTAGE 15kV
3. POWER FREQUENCY WITHSTAND 50kV
4. BASIC IMPULSE LEVEL 110KV
5. NOMINAL CURRENT RATING 2000 AMPS
6. CREEP DISTANCE 15.75"/400 mm (27 mm/kV)
7. TEMPERATURE CLASSIFICATION..... -50°C TO +105°C
8. WEIGHT (APPROXIMATE) 39.0 lbs (17.7 kg)



H-J INTERNATIONAL, INC.
3010 HIGH RIDGE BLVD, HIGH RIDGE, MO. 63049 USA
PHONE 1-636-677-3421 FAX 1-636-376-1915

*POWER APPARATUS
BUSHING*
15kV / 2000A

| | | |
|--|-------------------------------------|-------|
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF H-J INTERNATIONAL, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF H-J INTERNATIONAL, INC. IS STRICTLY PROHIBITED. BREAK ALL SHARPS UNLESS OTHERWISE NOTED | TOLERANCES (EXCEPT AS NOTED) | |
| | ONE PLACE MM | ±1.50 |
| | TWO PLACE MM | ±0.75 |
| | TWO PLACE DEC. | ±.060 |
| | THREE PLACE DEC. | ±.030 |
| FRACTIONS | ± 1/16" | |
| ANGLES | 2° | |

| | | | |
|--------------|-------------|------|---------|
| APPROVED BY | DB | DATE | 4-23-04 |
| CHECKED BY | RM | DATE | 4-23-04 |
| DRAWN BY | DB | DATE | 4-23-04 |
| TOOL NO. | T20-201-0 | | |
| PRODUCT GRP. | 2000 SERIES | | |

| | | | |
|-------------|-----|------------|--------|
| DRAWING NO. | | 20-201-000 | |
| SCALE | 1:4 | SIZE | B |
| REV. | | SHEET | 1 OF 1 |