



DIMENSIONS IN PARENTHESIS ARE METRIC

CONN. CODE "X"	CONDUCTOR SIZE		CONNECTOR DIA	CRIMPING INFO
	STD OR COMPRESSED	SOLID OR COMPACTED		MANUFACTURER, DIE, (CRIMPS)
3	2	1	.625 [15.8]	HUBBELL (ANDERSON); VERSACRIMP (5) BURNDY; BG (6), W-BG (3), W243 (4), U-BG (3), U243 (2)
4	1	1/0		KEARNEY; 5/8 NOSE (6), 5/8-1 (6), 9/16 (4), TU (4)
5	1/0	2/0		
6	2/0	3/0		
7	3/0	4/0	.780 [19.8]	HUBBELL (ANDERSON); VERSACRIMP (5) BURNDY; W247 (4), U247 (2), U27ART (3)
8	4/0	-		KEARNEY "D" 737 (7), 747 (4), "H" 737 (4), 747 (3)

RATINGS

MAX CONTINUOUS VOLTAGE		CONTINUOUS CURRENT
PHASE-TO-GND	PHASE-TO-PHASE	
15.2 kV	26.3 kV	200 AMPERE RMS
SHORT-TIME CURRENT RATINGS		FAULT CLOSE RATING
10kA RMS SYMETRIC FOR 0.17S		10kA RMS SYMETRIC FOR 0.17S
3.5kA RMS SYMETRIC FOR 3.00S		

INSULATION WITHSTAND VOLTAGES

BASIC IMPULSE LEVEL (1.2X50 MICROSEC. WAVE)	AC-60 HERTZ (ONE MINUTE)	DC (15 MINUTE)	PARTIAL DISCHARGE VOLTAGE (CEV)
125 kV CREST	40 kV RMS	78 kV	<3PC @ 19 kV

HUBBELL POWER SYSTEMS, INC.
8711 WADSWORTH ROAD, WADSWORTH, OHIO

PART NAME	ELBOW, 200A, 25KV SIZE 4 TP 225LE4XT	SCALE	.25=1
DESIGN	BVB	DATE	07/11/11
DRAWN	BVB	DATE	07/12/11
DWG. NO.	S --	REV. NO.	01