



REVISIONS					
REV	DATE	ECN #	DESCRIPTION	BY	APPROVED
1	12/6/2022	RMA F2208033	CLARIFIED MOUNTING HOLE OPTIONS & OTHER PART NUMBER CODE OPTIONS	CLS	AR

A CODE	GROOVE (DETAIL B)			
	d	b	t	D
0	WITHOUT / FLAT SURFACE			
1	100	8.1	3.9	116.2
2	100	7.2	3.6	114.4
3	96	9	4	114
4	89	5.6	3.9	100.2

00 CODE	MOUNTING HOLES
M1	M16 THREAD
18	$\phi 18$ mm THRU
WO	WITHOUT

C CODE	COATING
U	UNPAINTED
P	PAINTED

B CODE	SETTING DEVICE
C	LOCKABLE CAP
N	NON-LOCKABLE

D CODE	TEMPERATURE RANGE
S	-25°C TO 115°C (STANDARD)
L	-55°C TO 175°C (LOW)

ITEM	MATERIAL	FMS	FMH
1	FLANGE	MILD STEEL (S355J2G3)	STAINLESS STEEL AISI 316L
2	SPINDLE	STEEL	STAINLESS STEEL AISI 303
3	THRUST MEMBER	BRASS	EN AW6082 BLUE ANODIZED
4	THRUST SCREW	BRASS	EN AW6082 BLUE ANODIZED
5	CLAP	EN-GJL-200	EN-GJL-200
6	GASKET	HECKER CENTELLEN WS 3820	HECKER CENTELLEN WS 3820
7	O-RING	14 X 3 NBR 70	14 X 3 NBR 70
8	SNAP HEAD RIVET	STEEL	STEEL
9	LABEL	STAINLESS STEEL	STAINLESS STEEL
10	ROUND HEAD GROOVED PIN	STAINLESS STEEL	STAINLESS STEEL
11	O-RING	19 X 3 FKM	19 X 3 FKM
12	O-RING	28 X 5 FKM	28 X 5 FKM
13	LOCKING CAP	GFK / GRP - PA	GFK / GRP - PA
14	LOCKING RING	PA	PA



NOTE:
1. STANDARDS: EN 50216-8 / DIN 42560

THIRD ANGLE

TOLERANCES (EXCEPT AS NOTED) DIMENSIONS IN mm

DECIMAL

±

FRACTIONAL

±

ANGULAR

±

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE H-J FAMILY OF COMPANIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE H-J FAMILY OF COMPANIES IS PROHIBITED.



THE H-J FAMILY OF COMPANIES
3010 HIGH RIDGE BLVD. HIGH RIDGE, MO. 63049 USA
PHONE 1-636-677-3421 FAX 1-636-376-1915

**RADIATOR VALVE FLANGED
METAL-TO-METAL FMS/FMH TYPES**

MATERIAL SEE DRAWING

CHK'D - APP'D 12/22/21 DRAWING NO.

DRAWN BY CLS

DATE 12/22/2021

SCALE N.T.S.

RV-FMX-XX-A-00-B-C-D